

G&W社製送受波器の機能及び主要性能一覧表

日本エアークラフトサプライ(株) 2005年4月28日

Model		機能・用途					周波数範囲		ビーム・パターン(度)	
		Echo Sounder	Transponder	Side Scan	Hydrophone	Omni Projector	Low (kHz)	High (kHz)	horizontal Wide	vertical Narrow
1	147	○	—	—	—	—	24 ~ 50	—	17 ~ 23	—
2	152	○	—	—	—	—	24 ~ 38	—	14 ~ 23	9 ~ 15
3	142	○	—	—	—	—	—	160 ~ 600	—	5 ~ 12
4	T18	○	—	—	—	—	—	120	16.5	10.5
5	T37/T28	○	—	—	—	—	—	200	6.0	3.1
6	T27	○	—	—	—	—	12	—	33	33
7	76	○	—	—	—	—	24 ~ 38	160 ~ 600	14 ~ 23	5 ~ 12
8	T22	○	○	—	—	○	2	—	omni	—
9	T36/T61	—	—	○	—	—	100	500	1 & 0.3	40
10	T62/3/4	—	—	○	—	—	100	500	1 & 0.3	40
11	T30	—	○	—	—	○	50 ~ 60	—	omni	180
12	T43	—	○	—	—	○	45 ~ 61	—	omni	180
13	T54	—	○	—	—	○	8 ~ 16	—	omni	180
14	B1/200	—	-	-	○	-	-	0.1 ~ 150	omni	omni
15	D/11	—	○	-	○	○	0.1 ~ 20	-	omni	omni
16	D/17P	—	○	-	○	○	0.1 ~ 30	-	omni	omni
17	D/26P	—	○	-	○	○	0.1 ~ 45	-	omni	omni
18	D/70	—	-	-	○	○	0.1 ~ 100	-	omni	omni
19	D/70/H	—	-	-	○	○	0.1 ~ 100	-	omni	omni
20	D/140	—	-	-	○	○	-	0.1 ~ 200	omni	omni
21	D/140/H	—	-	-	○	○	-	0.1 ~ 200	omni	omni
22	D/300	—	-	-	○	-	-	0.1 ~ 500	omni	omni